



▶ **ESB DT-360 (Soft Dome Tweeter):**

Nominal Diameter: 25 mm
Dome Type: Silk
Power: 100 W RMS
Sensitivity: 91 dB
Frequency Range: 2000 -22000 Hz
Magnet: Ferrite 255 g
Re: 6.0 Ohm
Fs: 1100 Hz
Le: 0.046 mH (10 KHz)
Overall Diameter: 100 mm
Mounting Diameter: 73 mm
Mounting Depth: 27 mm

▶ **ESB DT-380 (Soft Dome Tweeter):**

Nominal Diameter: 25 mm
Dome Type: Silk
Power: 100 W RMS
Sensitivity: 93 dB
Frequency Range: 2000 -22000 Hz
Magnet: Ferrite 510 g
Re: 6.0 Ohm
Fs: 1100 Hz
Le: 0.033 mH (10 KHz)
Overall Diameter: 100 mm
Mounting Diameter: 73 mm
Mounting Depth: 43 mm

▶ **ESB DT-400 (Soft Dome Tweeter):**

Nominal Diameter: 25 mm
Impedance: 4 Ohm
Dome Type: Silk
Power: 100 W RMS
Sensitivity: 93 dB
Frequency Range: 2000 -20000 Hz
Magnet: Neodimium 18 g
Overall Diameter: 52 mm
Mounting Diameter: 45.5 mm
Mounting Depth: 15.5 mm

▶ **ESB UMA-800 (Dome Mid-High Unit):**

Nom. Diameter: 26 mm Tw, 43 mm Mid
Dome Type: Silk
Power: 100 W RMS
Sensitivity: 91 dB
Frequency Range: 1000 -22000 Hz
Re: 6 Ohm Tw, 5.2 Ohm Mid
Fs: 1100 Hz Tw, 600 Hz Mid
Le: 0.46 mH Tw (10 KHz)
0.14 mH Tw (10 KHz)
Overall Diameter: 136 x 205 mm
Mount. Diameter: 73 mm Tw, 91 mm Mid
Mounting Depth: 28 mm

▶ **ESB DM-450 (Soft Dome Midrange):**

Nominal Diameter: 43 mm
Impedance: 8 Ohm
Dome Type: Silk
Power: 100 W RMS
Sensitivity: 91 dB
Frequency Range: 1000 -10000 Hz
Re: 5.2 Ohm - Fs: 600 Hz
Le: 0.14 mH (10 KHz)
Overall Diameter: 130 mm
Mounting Diameter: 91 mm
Mounting Depth: 28 mm

▶ **ESB DM-600 (Soft Dome Midrange):**

Nominal Diameter: 50 mm
Impedance: 8 Ohm
Dome Type: Silk
Power: 175 W RMS
Sensitivity: 92.5 dB
Frequency Range: 800 -8000 Hz
Re: 6.2 Ohm
Fs: 350 Hz
Le: 0.14 mH (10 KHz)
Overall Diameter: 135 mm
Mounting Diameter: 99 mm
Mounting Depth: 48 mm

▶ **ESB CM-750 (Cone Midrange):**

Nominal Diameter: 130 mm
Impedance: 4 Ohm
Power: 100 W RMS
Sensitivity: 94 dB
Frequency Range: 120 - 3000 Hz
Re: 3.1 Ohm - Fs: 97 Hz - BL: 5.9 W/m
Vas: 3.01 lts - Qms: 2.57 - Qes: 0.42
Qts: 0.36 - Le: 0.27 mH (1 KHz)
Overall Diameter: 129 mm
Mounting Diameter: 112 mm
Mounting Depth: 59 mm

▶ **ESB 1000-MB (Cone Mid-Woofer):**

Nominal Diameter: 160 mm
Impedance: 4 Ohm
Power: 100 W RMS
Sensitivity: 94 dB
Frequency Range: 80 - 2000 Hz
Re: 3.7 Ohm - Fs: 78 Hz - BL: 5.4 W/m
Vas: 9.75 lts - Qms: 2.87 - Qes: 0.65
Qts: 0.53 - Le: 0.46 mH (1 KHz)
Overall Diameter: 170 mm
Mounting Diameter: 144 mm
Mounting Depth: 67 mm

▶ **ESB 1200-MB (Cone Mid-Woofer):**

Nominal Diameter: 160 mm
Impedance: 4 Ohm
Power: 80 W RMS
Sensitivity: 94 dB
Frequency Range: 55 - 4000 Hz
Re: 3.2 Ohm - Fs: 55 Hz - BL: 5.3 W/m
Vas: 19 lts - Qms: 3.64 - Qes: 0.43
Qts: 0.39 - Le: 0.45 mH (1 KHz)
Overall Diameter: 170 mm
Mounting Diameter: 144 mm
Mounting Depth: 74 mm

▶ **ESB 210-WS (Cone Woofer):**

Nominal Diameter: 200 mm
Impedance: 4 Ohm
Power: 100 W RMS
Sensitivity: 95 dB
Frequency Range: 40 - 1000 Hz
Re: 3.8 Ohm - Fs: 50 Hz - BL: 10.5 W/m
Vas: 23.17 lts - Qms: 3.01 - Qes: 0.31
Qts: 0.29 - Le: 0.71 mH (1 KHz)
Overall Diameter: 209 mm
Mounting Diameter: 179 mm
Mounting Depth: 87 mm

▶ **ESB 300-S2 (Cone Subwoofer):**

Nominal Diameter: 320 mm
Impedance: 2 x 4 Ohm
Power: 200 + 200 W RMS
Sensitivity: 103 dB
Frequency Range: 30 - 400 Hz
Re: 1.5 Ohm - Fs: 48 Hz - BL: 8.7 W/m
Vas: 73 lts - Qms: 2.72 - Qes: 0.35
Qts: 0.31 - Le: 0.24 mH (1 KHz)
Overall Diameter: 317 mm
Mounting Diameter: 285 mm
Mounting Depth: 151 mm

▶ **ESB 480-S2 (Cone Subwoofer):**

Nominal Diameter: 460 mm
Impedance: 2 x 4 Ohm
Power: 400 + 400 W RMS
Sensitivity: 105.5 dB
Frequency Range: 20 - 400 Hz
Re: 1.6 Ohm - Fs: 31 Hz - BL: 12.7 W/m
Vas: 392 lts - Qms: 2.38 - Qes: 0.24
Qts: 0.22 - Le: 0.38 mH (1 KHz)
Overall Diameter: 460 mm
Mounting Diameter: 416 mm
Mounting Depth: 190 mm