

Tweeter Type: Silk Dome
 Nominal Diameter: 1"/25 mm
 Woofer Type: Carbon Cone
 Nominal Diameter: 4"/100 mm
 Nominal Impedance (Znom): 4 Ohms
 Continuous Power Handling: 60 W
 Peak Power Handling: 120 W
 Frequency Response: 75 Hz - 25 KHz
 Sensitivity: 88.0 dB @ 1W/1m
 91.0 dB @ 2.83V/1m

TWEETER PARAMETERS

Magnet: Neodymium
 Voice Coil Diameter: 25.4 mm
 Voice Coil Resistance (Re): 3.6 Ohms

WOOFER PARAMETERS

Voice Coil Resistance (Re): 3.75 Ohms
 Free Air Resonance (Fs): 99.1 Hz
 Reference Efficiency (no): 0.356 %
 Electrical "Q" (Qes): 0.375
 Mechanical "Q" (Qms): 9.164
 Total Speaker "Q" (Qts): 0.360
 Equivalent Compliance (Vas): 1.43 lt
 Moving Mass (Mms): 7.128 g
 Mech. Compliance (Cms): 0.362 mm/N
 Magnetic Strength (BL): 6.659 N/A
 Effective Piston Area (Sd): 52.81 sq. cm

