

Speaker Type: Convertible Speaker
 Nominal Diameter: 6x9"/150x230 mm
 Nominal Impedance (Znom): 4 Ohms
 Continuous Power Handling: 120 W
 Peak Power Handling: 240 W
 Sensitivity: 88.5 dB @ 1W/1m
 91.5 dB @ 2.83V/1m
 Rec. Amplifier Power: 40 - 200W (RMS)

TWEETER PARAMETERS

Voice Coil Resistance (Re): 3.71 Ohms
 Free Air Resonance (Fs): 1300 Hz
 Electrical "Q" (Qes): 1.686
 Mechanical "Q" (Qms): 1.129
 Total Speaker "Q" (Qts): 0.676

WOOFER PARAMETERS

Voice Coil Resistance (Re): 3.14 Ohms
 Free Air Resonance (Fs): 58.9 Hz
 Reference Efficiency (no): 0,446 %
 Electrical "Q" (Qes): 1.302
 Mechanical "Q" (Qms): 3.744
 Total Speaker "Q" (Qts): 0.966
 Equivalent Compliance (Vas): 27.79 lt
 Moving Mass (Mms): 16.89 g
 Mech. Compliance (Cms): 0.432 mm/N
 Magnetic Strength (BL): 4.19 N/A
 Effective Piston Area (Sd): 213.13 sq. cm
 One-Way Linear Excursion (Xmax): 3.25 mm

