

Speaker Type: Component Midrange
 Nominal Diameter: 4"/100 mm
 Nominal Impedance (Znom): 4 Ohms
 Continuous Power Handling: 100 W
 Peak Power Handling: 200 W
 Rec. Amplifier Power: 40 - 150W (RMS)

PARAMETERS

Voice Coil Resistance (Re): 3.87 Ohms
 Voice Coil Diameter: 25.4 mm
 Free Air Resonance (Fs): 77 Hz
 Reference Efficiency (no): 0.24 %
 Sensitivity: 86.2 dB @ 1W/1m
 89.2 dB @ 2.83V/1m
 Electrical "Q" (Qes): 0.75
 Mechanical "Q" (Qms): 4.965
 Total Speaker "Q" (Qts): 0.651
 Equivalent Compliance (Vas): 4.15 lt
 Moving Mass (Mms): 4.47 g
 Mech. Compliance (Cms): 0.955 mm/N
 Magnetic Strength (BL): 3.344 N/A
 Effective Piston Area (Sd): 55.42 sq. cm
 One-Way Linear Excursion (Xmax): 2.6 mm

DESIGN BANDWIDTH

With 48 dB/oct. HP filters: 130 Hz - 7 KHz
 With 24 dB/oct. HP filters: 170 Hz - 7 KHz
 With 12 dB/oct. HP filters: 210 Hz - 7 KHz

